

Fiche technique

040C2026-8

Boîte à boutons aluminium M10 200x260x85, sans trous, sans entrée câble



Caractéristiques

Portée	Boîtiers à boutons aluminium M10 200x260 mm
Composant	Couvercle sans trous
Code	040C2026-8
Désignation des marchandises	Boîte à boutons aluminium M10 200x260x85, sans trous, sans entrée câble
Couleur	Grigio RAL7016 / Grigio RAL7035
Poids	1608,0
Tarif douanier	85381000
GTIN	8052878045883

Données techniques

Approvals	CE, UL, CSA
UL/CSA Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Diecasting
Enclosure material	Aluminum Al Si11 Cu2 (EN AC46100)
Gasket material	Nitrile rubber
Screw material	Zamak zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Tightening torque	3Nm (26.6 Lb-in)
Painting	Polyester powder coating (except unpainted models)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

Dessins techniques

