

Scheda Dati

040C2320-1ES9

Doos knoppenbord aluminium M4 230x205x100, 9 gaten Ø 30, met kabelingang



Caratteristiche

| | |
|-------------------------|--|
| Bereik | Dozen knoppenbord aluminium M4 230x205 mm |
| Componente | Deksel met 9 gaten Ø 30 |
| Rubriek | 040C2320-1ES9 |
| Omschrijving | Doos knoppenbord aluminium M4 230x205x100, 9 gaten Ø 30, met kabelingang |
| Kleur | Grigio RAL7035 |
| Peso | 1841,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878046118 |

Dati tecnici

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| UL/CSA Approval | Item will be labelled only upon specific request |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Operating temperatures | -40° ÷ +100°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK09 (IEC-EN62262) |
| Manufacturing process | Shell gravity diecasting |
| Enclosure material | Aluminum Al Si12 Cu (EN AC47000) |
| Gasket material | Cork rubber |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 2,5Nm (22.1 Lb-in) |
| Painting | Polyester powder coating (except unpainted models) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

