

## Fiche technique

040C2320-8E

Boîte à boutons aluminium M4 230x205x80, sans trous, avec entrée câble



## Caractéristiques

|                                     |                                                                        |
|-------------------------------------|------------------------------------------------------------------------|
| <b>Portée</b>                       | Boîtiers à boutons aluminium M4 230x205 mm                             |
| <b>Composant</b>                    | Couvercle sans trous                                                   |
| <b>Code</b>                         | 040C2320-8E                                                            |
| <b>Désignation des marchandises</b> | Boîte à boutons aluminium M4 230x205x80, sans trous, avec entrée câble |
| <b>Couleur</b>                      | Grigio RAL7035                                                         |
| <b>Poids</b>                        | 1620,0                                                                 |
| <b>Tarif douanier</b>               | 85381000                                                               |
| <b>GTIN</b>                         | 8052878046231                                                          |

## Données techniques

|                                          |                                                    |
|------------------------------------------|----------------------------------------------------|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>UL/CSA Approval</b>                   | Item will be labelled only upon specific request   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -40° ÷ +100°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Manufacturing process</b>             | Shell gravity diecasting                           |
| <b>Enclosure material</b>                | Aluminum Al Si12 Cu (EN AC47000)                   |
| <b>Gasket material</b>                   | Cork rubber                                        |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Tightening torque</b>                 | 2,5Nm (22.1 Lb-in)                                 |
| <b>Painting</b>                          | Polyester powder coating (except unpainted models) |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                              |
| <b>Fitted for outdoor application</b>    | yes                                                |
| <b>Warranty period</b>                   | 18 months                                          |

## Dessins techniques

---

