

Scheda Dati

040C2325-1N

Caja botonera aluminio M4 230x257x100, en bruto, sin orificios, sin entrada cable



Caratteristiche

Rango	Cajas botoneras aluminio M4 230x257 mm
Componente	Tapa sin orificios
Código	040C2325-1N
Descripción	Caja botonera aluminio M4 230x257x100, en bruto, sin orificios, sin entrada cable
Color	Non Verniciato
Peso	2186,0
Tariffa doganale	85381000
GTIN	8052878046552

Dati tecnici

Approvals	CE, UL, CSA, EAC
UL/CSA Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Shell gravity diecasting
Enclosure material	Aluminum Al Si12 Cu (EN AC47000)
Gasket material	Cork rubber
Screw material	Stainless steel AISI 304
Tightening torque	2,5Nm (22.1 Lb-in)
Painting	Polyester powder coating (except unpainted models)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

Disegni tecnici

