

Scheda Dati

040C2325-1P24

Doos knoppenbord aluminium M4 230x257x100, 24 gaten Ø 22, zonder kabelingang



Caratteristiche

Bereik	Dozen knoppenbord aluminium M4 230x257 mm
Componente	Deksel met 24 gaten Ø 22
Rubriek	040C2325-1P24
Omschrijving	Doos knoppenbord aluminium M4 230x257x100, 24 gaten Ø 22, zonder kabelingang
Kleur	Grigio RAL7035
Peso	2114,0
Tariffa doganale	85381000
GTIN	8052878046613

Dati tecnici

Approvals	CE, UL, CSA, EAC
UL/CSA Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Shell gravity diecasting
Enclosure material	Aluminum Al Si12 Cu (EN AC47000)
Gasket material	Cork rubber
Screw material	Stainless steel AISI 304
Tightening torque	2,5Nm (22.1 Lb-in)
Painting	Polyester powder coating (except unpainted models)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

Disegni tecnici

