

Scheda Dati

040C3226-12P36

Boîte à boutons aluminium M5 320x265x120, avec 36 trous Ø 22, sans entrée câble



Caratteristiche

| | |
|-------------------------------------|---|
| Portée | Boîtiers à boutons aluminium M5 320x265 mm |
| Componente | Couvercle avec 36 trous Ø 22 |
| Code | 040C3226-12P36 |
| Désignation des marchandises | Boîte à boutons aluminium M5 320x265x120, avec 36 trous Ø 22, sans entrée câble |
| Couleur | Grigio RAL7016 / Grigio RAL7035 |
| Peso | 4232,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878046927 |

Dati tecnici

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| UL/CSA Approval | Item will be labelled only upon specific request |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Operating temperatures | -40° ÷ +100°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK09 (IEC-EN62262) |
| Manufacturing process | Shell gravity diecasting |
| Enclosure material | Aluminum Al Si12 Cu (EN AC47000) |
| Gasket material | Cork rubber |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 2,5Nm (22.1 Lb-in) |
| Painting | Polyester powder coating (except unpainted models) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

