

## Scheda Dati

040D1416-6

Aftakdoos aluminium 142x166x64



## Caratteristiche

<b>Bereik</b>	Aftakdozen aluminium 142x166 mm
<b>Componente</b>	Aftakdoos 142x166
<b>Rubriek</b>	040D1416-6
<b>Omschrijving</b>	Aftakdoos aluminium 142x166x64
<b>Kleur</b>	Grigio RAL7040
<b>Peso</b>	560,0
<b>Tariffa doganale</b>	85381000
<b>GTIN</b>	8052878047016

## Dati tecnici

<b>Approvals</b>	CE, EAC
<b>Compliance with standards</b>	CEI EN60670, CEI EN60670-22, CEI EN23-48
<b>Operating temperatures</b>	-25° ÷ +90°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK08 (IEC-EN62262)
<b>Enclosure material</b>	Aluminium alloy EN AB 461H0 (UNI EN 1676)
<b>Gasket material</b>	Polyurethane foam
<b>Screw material</b>	Stainless steel AISI 304
<b>Tightening torque</b>	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
<b>Painting</b>	Polyester powder coating
<b>Mist saline resistance</b>	500 hours (ASTM B117) / 700 hours (ISO 9227)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Disegni tecnici

