

## Datasheet

040X0820-8

Stainless steel push-button enclosure 82x202x85, undrilled, without cable entry



## Features

<b>Range</b>	Stainless steel push-button enclosures 82x202 mm
<b>components</b>	Undrilled lid
<b>Code</b>	040X0820-8
<b>Description</b>	Stainless steel push-button enclosure 82x202x85, undrilled, without cable entry
<b>Weight - gr</b>	826.0
<b>Customs Tariff</b>	85381000
<b>GTIN</b>	8052878048105

## Datasheet

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-40° ÷ +100°C
<b>Protection degree</b>	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Enclosure material</b>	Stainless steel AISI 316L
<b>Gasket material</b>	Polyurethane foam
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	M5 - cross head Phillips 2
<b>Tightening torque</b>	2,5Nm (22.1 Lb-in)
<b>Protection against electric shock</b>	Class I (IEC-EN61140)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Technical drawings

---

