# Datasheet

040X0820-8P6
Stainless steel push-button enclosure 82x202x85, 6 holes Ø 22, without cable entry



## Features

| | |
|---|---|
| **Range** | Stainless steel push-button enclosures 82x202 mm |
| **components** | 6-hole lid Ø 22 |
| **Code** | 040X0820-8P6 |
| **Description** | Stainless steel push-button enclosure 82x202x85, 6 holes Ø 22, without cable entry |
| **Weight - gr** | 735.0 |
| **Customs Tariff** | 85381000 |
| **GTIN** | 8052878048136 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-EN62208 |
| **Operating temperatures** | -40° ÷ +100°C |
| **Protection degree** | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| **Protection against impact** | IK07 (IEC-EN62262) |
| **Enclosure material** | Stainless steel AISI 316L |
| **Gasket material** | Polyurethane foam |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | M5 - cross head Phillips 2 |
| **Tightening torque** | 2,5Nm (22.1 Lb-in) |
| **Protection against electric shock** | Class I (IEC-EN61140) |
| **Fitted for outdoor application** | yes |
| **Warranty period** | 18 months |

## Technical drawings

