

## Scheda Dati

040X0820-8P6

Painikepaneelikotelo ruostumaton teräs 82x202x85, 6 aukkoa Ø 22, ilman kaapelin sisäänmenoa



## Caratteristiche

Range	Painikepaneelikotelo ruostumaton teräs 82x202 mm
Componente	Kansi 6 aukolla Ø 22
Code	040X0820-8P6
Kuvaus	Painikepaneelikotelo ruostumaton teräs 82x202x85, 6 aukkoa Ø 22, ilman kaapelin sisäänmenoa
Peso	735,0
Tariffa doganale	85381000
GT	8052878048136

## Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN62208
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK10 (IEC-EN62262)
Enclosure material	Stainless steel AISI 316L
Gasket material	Polyurethane foam
Screw material	Stainless steel AISI 304
Screw type	M5 - cross head Phillips 2
Tightening torque	2,5Nm (22.1 Lb-in)
Protection against electric shock	Class I (IEC-EN61140)
Fitted for outdoor application	yes
Warranty period	18 months

## Disegni tecnici

