


## Datablad

### 050ASPD11

Veiligheidsvoorziening eenfasig knipperend, zonder led, 1 N.O. + 1 N.C.



## Kenmerken

|                     |   |
|---------------------|---|
| <b>Bereik</b>       | Knipperende veiligheidsvoorziening                                      |
| <b>Component</b>    | Eenfasige knipperende veiligheidsvoorzieningen                          |
| <b>Rubriek</b>      | 050ASPD11   |
| <b>Omschrijving</b> | Veiligheidsvoorziening eenfasig knipperend, zonder led, 1 N.O. + 1 N.C. |
| <b>Kleur</b>        | Rosso   |
| <b>Gewicht</b>      | 120,0   |
| <b>Douanetarief</b> | 85365080  |
| <b>GTIN</b>         | 8052878048587   |

## Technische gegevens

|  |  |
|--|--|
| <b>Approvals</b>                             | CE   |
| <b>Compliance with standards</b>             | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Operating temperatures</b>                | -25° ÷ +65°C                                     |
| <b>Environmental operating values</b>        | all climates +40°C and 92% RH                    |
| <b>Protection degree</b>                     | IP20 (IEC-EN60529)                               |
| <b>Protection against impact</b>             | IK03 (IEC-EN62262)                               |
| <b>Mechanical durability</b>                 | 1.000.000 Operations                             |
| <b>Shock resistance</b>                      | 30g duration=18ms (EN-IEC 60068-2-27)            |
| <b>Shock resistance</b>                      | 50g duration=11ms (EN-IEC 60068-2-27)            |
| <b>Vibration resistance</b>                  | 5g f= 2...500Hz (EN-IEC 60068-2-6)               |
| <b>Contact blocks configuration</b>          | Max no. 2 blocks (1+1)                           |
| <b>Material</b>                              | PA Polyamide                                     |
| <b>Lens material</b>                         | PC Polycarbonate                                 |
| <b>Locking ring material</b>                 | Zamak zinc alloy                                 |
| <b>Actuation type</b>                        | Spring return                                    |
| <b>Rated insulation voltage</b>              | Ui 690V - Uimp 4KV (IEC-EN60947-1)               |
| <b>Protection against electric shock</b>     | Class II (IEC-EN61140)                           |
| <b>Signalling type</b>                       | Flashing   |
| <b>Led bulb type</b>                         | Ba9S red flashing bulb 24V AC/DC included        |
| <b>Model 050ASPD11 without Ba9s Led bulb</b> | Customizable with appropriate Led voltage        |

---

**Contact block characteristics**

See items 020PD911,020PD901, 020PD910

---

**Warranty period**

18 months

---

## Technische tekeningen

