


Scheda Dati

050ASPLD01

Dispositivo di sicurezza monofase lampeggiante, con led rosso 24V, AC/DC, 1 N.C.



Caratteristiche

| | |
|-------------------------|-------------------------------------------------|
| Gamma | Dispositivi di sicurezza lampeggianti |
| Componente | Dispositivi di sicurezza monofase lampeggianti |
| Codice | 050ASPLD01 |
| Descrizione | Dispositivo di sicurezza monofase lampeggiante, |
| Colore | Rosso |
| Peso | 115,0 |
| Tariffa doganale | 85365080 |
| GTIN | 8052878048594 |

Dati tecnici

| | |
|----------------------------------------------|--------------------------------------------------|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | all climates +40°C and 92% RH |
| Protection degree | IP20 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 2 blocks (1+1) |
| Material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | Zamak zinc alloy |
| Actuation type | Spring return |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Signalling type | Flashing |
| Led bulb type | Ba9S red flashing bulb 24V AC/DC included |
| Model 050ASPD11 without Ba9s Led bulb | Customizable with appropriate Led voltage |
| Contact block characteristics | See items 020PD911,020PD901, 020PD910 |

Warranty period

18 months

Disegni tecnici

