



Fiche technique

050ASPLD10

Dispositif de sécurité monophasé clignotant, avec led rouge 24V, AC/DC, 1 N.O.



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Dispositifs de sécurité clignotants |
| Composant | Dispositifs de sécurité monophasé clignotants |
| Code | 050ASPLD10 |
| Désignation des marchandises | Dispositif de sécurité monophasé clignotant, avec led rouge 24V, AC/DC, 1 N.O. |
| Couleur | Rosso |
| Poids | 115,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878048600 |

Données techniques

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +65°C |
| Environmental operating values | all climates +40°C and 92% RH |
| Protection degree | IP20 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 2 blocks (1+1) |
| Material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | Zamak zinc alloy |
| Actuation type | Spring return |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Signalling type | Flashing |
| Led bulb type | Ba9S red flashing bulb 24V AC/DC included |
| Model 050ASPD11 without Ba9s Led bulb | Customizable with appropriate Led voltage |

Contact block characteristics

See items 020PD911,020PD901, 020PD910

Warranty period

18 months

Dessins techniques

