


## Scheda Dati

050ASPLD11

Dispositivo di sicurezza monofase lampeggiante, con led rosso 24V, AC/DC, 1 N.O. + 1 N.C.



## Caratteristiche

<b>Gamma</b>	Dispositivi di sicurezza lampeggianti
<b>Componente</b>	Dispositivi di sicurezza monofase lampeggianti
<b>Codice</b>	050ASPLD11
<b>Descrizione</b>	Dispositivo di sicurezza monofase lampeggiante,
<b>Colore</b>	Rosso
<b>Peso</b>	125,0
<b>Tariffa doganale</b>	85365080
<b>GTIN</b>	8052878048617

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Environmental operating values</b>	all climates +40°C and 92% RH
<b>Protection degree</b>	IP20 (IEC-EN60529)
<b>Protection against impact</b>	IK03 (IEC-EN62262)
<b>Mechanical durability</b>	1.000.000 Operations
<b>Shock resistance</b>	30g duration=18ms (EN-IEC 60068-2-27)
<b>Shock resistance</b>	50g duration=11ms (EN-IEC 60068-2-27)
<b>Vibration resistance</b>	5g f= 2...500Hz (EN-IEC 60068-2-6)
<b>Contact blocks configuration</b>	Max no. 2 blocks (1+1)
<b>Material</b>	PA Polyamide
<b>Lens material</b>	PC Polycarbonate
<b>Locking ring material</b>	Zamak zinc alloy
<b>Actuation type</b>	Spring return
<b>Rated insulation voltage</b>	Ui 690V - Uimp 4KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Signalling type</b>	Flashing
<b>Led bulb type</b>	Ba9S red flashing bulb 24V AC/DC included
<b>Model 050ASPD11 without Ba9s Led bulb</b>	Customizable with appropriate Led voltage

---

**Contact block characteristics**

See items 020PD911,020PD901, 020PD910

---

**Warranty period**

18 months

---

## Disegni tecnici

