


Scheda Dati

050ASPLD11

Dispositivo di sicurezza monofase lampeggiante, con led rosso 24V, AC/DC, 1 N.O. + 1 N.C.



Caratteristiche

Gamma	Dispositivi di sicurezza lampeggianti
Componente	Dispositivi di sicurezza monofase lampeggianti
Codice	050ASPLD11
Descrizione	Dispositivo di sicurezza monofase lampeggiante,
Colore	Rosso
Peso	125,0
Tariffa doganale	85365080
GTIN	8052878048617

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Environmental operating values	all climates +40°C and 92% RH
Protection degree	IP20 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 2 blocks (1+1)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Actuation type	Spring return
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Signalling type	Flashing
Led bulb type	Ba9S red flashing bulb 24V AC/DC included
Model 050ASPD11 without Ba9s Led bulb	Customizable with appropriate Led voltage

Contact block characteristics

See items 020PD911,020PD901, 020PD910

Warranty period

18 months

Disegni tecnici

