

Scheda Dati

050C7

Kaksinapainen naarasliitin



Caratteristiche

Range	Rajakytkin ja kaapelit
Componente	Kaksinapainen naarasliitin
Code	050C7
Kuvaus	Kaksinapainen naarasliitin
Väriä	Grigio RAL7035
Peso	16,0
Tariffa doganale	85365080
GT	8052878048624

Dati tecnici

Approvals	050C7V2: CE, UL, CSA, / 050C7: CE only
Compliance with standards	IEC-EN60320-1 - SHAPE C7
Operating temperatures	-25° ÷ +70°C
Protection degree	IP20 (IEC-EN60529)
Housing material	PC Polycarbonate
Female contact material	Zinc plated brass
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Electrical ratings	250V - 2A max
Cover screw tightening torque	0.2 ÷ 0.5Nm (1.8÷4.4 Lb-in)
Terminal screw tightening torque	0.2 ÷ 0.5Nm (1.8÷4.4 Lb-in)
Terminal screw capacity	Single core cable: 0.5÷1.5mm ² (20÷15 AWG)
Cable entry	050C7V2: 2x D.5mm - 050C7: 1xD.7mm
Warranty period	18 months

Disegni tecnici

