


## Datenblatt

050C7V2

Zweipoliger Steckverbinder weiblich, 2 Eingänge



## Merkmale

<b>Baureihe</b>	Endschalter und Kabel
<b>Komponenten</b>	Zweipolige Steckverbinder weiblich
<b>Artikel-Nr.</b>	050C7V2
<b>Beschreibung</b>	Zweipoliger Steckverbinder weiblich, 2 Eingänge
<b>Farbe</b>	Grigio RAL7035
<b>Gewicht - gr</b>	25,6
<b>Zolltarifnummer</b>	85365080
<b>GTIN</b>	8052878048648

## Technische Daten

<b>Approvals</b>	050C7V2: CE, UL, CSA, / 050C7: CE only
<b>Compliance with standards</b>	IEC-EN60320-1 - SHAPE C7
<b>Operating temperatures</b>	-25° ÷ +70°C
<b>Protection degree</b>	IP20 (IEC-EN60529)
<b>Housing material</b>	PC Polycarbonate
<b>Female contact material</b>	Zinc plated brass
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Electrical ratings</b>	250V - 2A max
<b>Cover screw tightening torque</b>	0.2 ÷ 0.5Nm (1.8÷4.4 Lb-in)
<b>Terminal screw tightening torque</b>	0.2 ÷ 0.5Nm (1.8÷4.4 Lb-in)
<b>Terminal screw capacity</b>	Single core cable: 0.5÷1.5mm <sup>2</sup> (20÷15 AWG)
<b>Cable entry</b>	050C7V2: 2x D.5mm - 050C7: 1xD.7mm
<b>Warranty period</b>	18 months

## Technische Zeichnungen

