


Fiche technique

050C7V2

Connecteur bipolaire femelle à 2 voies



Caractéristiques

Portée	Interrupteurs de fin de course et câbles
Composant	Connecteurs bipolaires femelles
Code	050C7V2
Désignation des marchandises	Connecteur bipolaire femelle à 2 voies
Couleur	Grigio RAL7035
Poids	25,6
Tarif douanier	85365080
GTIN	8052878048648

Données techniques

Approvals	050C7V2: CE, UL, CSA, / 050C7: CE only
Compliance with standards	IEC-EN60320-1 - SHAPE C7
Operating temperatures	-25° ÷ +70°C
Protection degree	IP20 (IEC-EN60529)
Housing material	PC Polycarbonate
Female contact material	Zinc plated brass
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Electrical ratings	250V - 2A max
Cover screw tightening torque	0.2 ÷ 0.5Nm (1.8÷4.4 Lb-in)
Terminal screw tightening torque	0.2 ÷ 0.5Nm (1.8÷4.4 Lb-in)
Terminal screw capacity	Single core cable: 0.5÷1.5mm ² (20÷15 AWG)
Cable entry	050C7V2: 2x D.5mm - 050C7: 1xD.7mm
Warranty period	18 months

Dessins techniques

