

## Scheda Dati

050CB075A

Streng tweepolige kabel 2x0,75 mm<sup>2</sup>, L 100m, oranje



## Caratteristiche

|                         |   |
|-------------------------|---|
| <b>Bereik</b>           | Eindschakelaar en kabels  |
| <b>Componente</b>       | Streng tweepolige kabel 2x0,75 mm <sup>2</sup>                  |
| <b>Rubriek</b>          | 050CB075A   |
| <b>Omschrijving</b>     | Streng tweepolige kabel 2x0,75 mm <sup>2</sup> , L 100m, oranje |
| <b>Kleur</b>            | Arancio   |
| <b>Peso</b>             | 4300,0  |
| <b>Tariffa doganale</b> | 85444995  |
| <b>GTIN</b>             | 8052878048662   |

## Dati tecnici

|                                  |  |
|----------------------------------|--|
| <b>Approvals</b>                 | CE   |
| <b>Conductor</b>                 | Plain annealed copper acc.to CEI EN 60228 cl.5 |
| <b>Core insulation</b>           | PVC R2 acc.to CEI EN 50363-0                   |
| <b>Core colours</b>              | DIN 47100                                      |
| <b>Rated voltage</b>             | 300/500V                                       |
| <b>Test voltage</b>              | 2000V  |
| <b>Operating temperatures</b>    | -20° ÷ +70°C static                            |
| <b>Short circuit temperature</b> | 160°C max.                                     |
| <b>Insulation resistance</b>     | >100 MOhm/Km                                   |
| <b>Minimum bending radius</b>    | 10 times the cable diameter                    |
| <b>Cable skein lenght</b>        | 100m   |
| <b>Warranty period</b>           | 18 months                                      |

## Disegni tecnici

---

