

## Hoja de datos

050F02

Final de carrera de posición 2 N.C.



## Características

Rango	Final de carrera y cables
Componente	Finales de carrera bipolares
Código	050F02
Descripción	Final de carrera de posición 2 N.C.
Color	Rosso
Peso	69,0
Arancel aduanero	8536500700
GTIN	8052878048860

## Datos técnicos

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Compliance with standards	CENELEC EN 50047
Operating temperatures	-10° ÷ +80°C
Environmental operating values	all climates +40°C and 92% RH
Storage temperatures	-25° ÷ +85°C
Protection degree	IP67 (IEC-EN60529)
Mechanical durability	10.000.000 Operations
Housing material	PA Polyamide
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Cable entry	M20x1,5
Contact material	Ag 1000/1000
Contact movement	Slow action contact
NC contacts (all versions)	Positive opening function (IEC-EN60947-5-1 ann.K)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Rated thermal current	Ith 10A (IEC-EN60947-1)
Electrical ratings	AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508)
AC Performances	AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A
DC Performances	DC 24V-2.5A, 120V-0.6A, 240V-0.3A

---

<b>Type 050F02S</b>	With bracket and cable gland included
<b>Type 050F02SC</b>	Wired version with 2.5m of yellow cable 2x0.75mm <sup>2</sup>
<b>Warranty period</b>	18 months

---

# Dibujos técnicos

