

Scheda Dati

050F11

Interrupteur de fin de course de position 1 N.C. + 1 N.O.



Caratteristiche

| | |
|-------------------------------------|---|
| Portée | Interrupteurs de fin de course et câbles |
| Componente | Fins de course bipolaires |
| Code | 050F11 |
| Désignation des marchandises | Interrupteur de fin de course de position 1 N.C. + 1 N.O. |
| Couleur | Rosso |
| Peso | 67,91 |
| Tariffa doganale | 8536500700 |
| GTIN | 8052878048907 |

Dati tecnici

| | |
|---------------------------------------|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | CENELEC EN 50047 |
| Operating temperatures | -10° ÷ +80°C |
| Environmental operating values | all climates +40°C and 92% RH |
| Storage temperatures | -25° ÷ +85°C |
| Protection degree | IP67 (IEC-EN60529) |
| Mechanical durability | 10.000.000 Operations |
| Housing material | PA Polyamide |
| Terminal screw | Tightening torque 0.8÷1 Nm (IEC-EN60947-1) |
| Terminal screw head shape | Combined:cross Phillips2 or slotted flat D.5mm max |
| Terminal screw material | Zinc plated steel |
| Cable entry | M20x1,5 |
| Contact material | Ag 1000/1000 |
| Contact movement | Slow action contact |
| NC contacts (all versions) | Positive opening function (IEC-EN60947-5-1 ann.K) |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Rated thermal current | Ith 10A (IEC-EN60947-1) |
| Electrical ratings | AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508) |
| AC Performances | AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A |
| DC Performances | DC 24V-2.5A, 120V-0.6A, 240V-0.3A |

| | |
|------------------------|---|
| Type 050F02S | With bracket and cable gland included |
| Type 050F02SC | Wired version with 2.5m of yellow cable 2x0.75mm ² |
| Warranty period | 18 months |

Disegni tecnici

