

## Datenblatt

050PEL5C-24

Lineare Led-Deckenleuchte, 24V Ac/DC, 50/60HZ, 950 lm, L 598 mm, mit Verbinder



## Merkmale

<b>Baureihe</b>	Zusammenstellbare Meldeleuchtensäulen
<b>Komponenten</b>	Lineare Led-Deckenleuchte, 24V AC/DC, 50/60HZ, 950 lm
<b>Artikel-Nr.</b>	050PEL5C-24
<b>Beschreibung</b>	Lineare Led-Deckenleuchte, 24V Ac/DC, 50/60HZ, 950 lm, L 598 mm, mit Verbinder
<b>Farbe</b>	Grigio RAL7035
<b>Gewicht - gr</b>	494,0
<b>Zolltarifnummer</b>	85395200
<b>GTIN</b>	8052878049287

## Technische Daten

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60598-1, IEC-EN60598-2-1
<b>Compliance with standards</b>	IEC-EN62471
<b>Compliance to EMC standards</b>	EN55015, EN61000-3-2, EN61000-3-3, EN61547
<b>Compliance to directives</b>	2014/35/EU, 2014/30/EU, RoHS 2011/65/EU
<b>Environmental operating values</b>	all climates +40°C and 92% RH
<b>Storage temperatures</b>	-30° ÷ +70°C
<b>Operating temperatures</b>	-25° ÷ +60°C
<b>Protection degree</b>	IP40 (IEC-EN60529)
<b>Protection against impact</b>	IK06 (IEC-EN62262)
<b>Housing material</b>	PC Polycarbonate
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>LED light intensity - power consumption</b>	950 Lumen - 10W
<b>Operating voltage tolerance</b>	+10% / -20%
<b>LED electrical life</b>	50.000 hours
<b>LED colour temperature</b>	6000K
<b>DC Power supply</b>	No polarity needed
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV
<b>On-Off switch</b>	Built-in
<b>Light distribution</b>	Rotation of 180° - adjustable

---

<b>Power supply connector</b>	050C7V2 included, suitable for single lamp wiring
<b>Power supply connector</b>	or sequential wiring of max n°5 lamps
<b>Power supply connector characteristics</b>	See items: 050C7V2 - 050C7
<b>Light up possibility</b>	Through door limit switch - 050F02S
<b>Accessory</b>	050KFM Magnetic mounting kit
<b>Warranty period</b>	18 months

---

## Technische Zeichnungen

