

## Hoja de datos

050PPE8

Plafón lineal fluorescente con toma VDE, 8W, 240V, 50/60HZ, 200 lm, L 450 mm



## Características

|                         |  |
|-------------------------|--|
| <b>Rango</b>            | Plafones con tomas VDE   |
| <b>Componente</b>       | Plafón lineal fluorescente, toma VDE, 8W, 240V, 50/60HZ                      |
| <b>Código</b>           | 050PPE8  |
| <b>Descripción</b>      | Plafón lineal fluorescente con toma VDE, 8W, 240V, 50/60HZ, 200 lm, L 450 mm |
| <b>Color</b>            | Grigio RAL7035   |
| <b>Peso</b>             | 990,0  |
| <b>Arancel aduanero</b> | 85393980   |
| <b>GTIN</b>             | 8052878049423  |

## Datos técnicos

|  |   |
|--|---|
| <b>Approvals</b>                             | CE  |
| <b>Compliance with standards</b>             | IEC-EN60598-1, IEC-EN60598-2-1                      |
| <b>Compliance with standards</b>             | IEC-EN62471   |
| <b>Compliance to EMC standards</b>           | EN55015, EN61000-3-2, EN61000-3-3, EN61547          |
| <b>Compliance to directives</b>              | 2014/35/EU, 2014/30/EU, RoHS 2011/65/EU             |
| <b>Operating temperatures</b>                | -10° ÷ +50°C  |
| <b>Protection degree</b>                     | IP20 (IEC-EN60529)                                  |
| <b>Protection against impact</b>             | IK03 (IEC-EN62262)                                  |
| <b>Housing material</b>                      | Metal: Aluminum / Thermoplastic: PP Polypropylene   |
| <b>Protection against electric shock</b>     | Class I (IEC-EN61140)                               |
| <b>Operating voltage tolerance</b>           | -20% / +10%   |
| <b>Neon tube electrical life</b>             | 8.000 hours   |
| <b>Neon tube light intensity</b>             | Lumen 200 (8W) - Lumen 420 (13W)                    |
| <b>Neon tube type and colour temperature</b> | T5 - 6400K  |
| <b>Rated insulation voltage</b>              | Ui 300V - Uimp 2.5KV                                |
| <b>On-Off switch</b>                         | Built-in  |
| <b>Light up possibility</b>                  | Through door limit switch - 050F02S                 |
| <b>Accessory</b>                             | 050S019 Magnetic mounting plate                     |
| <b>Spare parts</b>                           | Neon tube 050TNE8(8W), 050TNE13(13W), 050TNE21(21W) |
| <b>Lamp wiring</b>                           | Included. 4m of orange cable 2x1.5 + 1x1.5mm2       |

---

|                        |                             |
|------------------------|-----------------------------|
| <b>Sockets</b>         | type CEE 7/3 - 250V-10A max |
| <b>Warranty period</b> | 18 months                   |

---

## Dibujos técnicos

