

Scheda Dati

050PPE8

Lineaarinen kattovalaisin loistevalolla VDE-liittimet, 8W, 240V, 50/60 HZ, 200 lm, L 450 mm



Caratteristiche

Range	Kattolamput VDE-liittimellä
Componente	Loistelamppu kattovalaisin, VDE-liittimet, 8W, 240V,50/60HZ
Code	050PPE8
Kuvaus	Lineaarinen kattovalaisin loistevalolla VDE-liittimet, 8W, 240V, 50/60 HZ, 200 lm, L 450 mm
Väriä	Grigio RAL7035
Peso	990,0
Tariffa doganale	85393980
GT	8052878049423

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60598-1,IEC-EN60598-2-1
Compliance with standards	IEC-EN62471
Compliance to EMC standards	EN55015, EN61000-3-2, EN61000-3-3, EN61547
Compliance to directives	2014/35/EU, 2014/30/EU, RoHS 2011/65/EU
Operating temperatures	-10° ÷ +50°C
Protection degree	IP20 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Housing material	Metal: Aluminum / Thermoplastic: PP Polypropylene
Protection against electric shock	Class I (IEC-EN61140)
Operating voltage tolerance	+10% / -20%
Neon tube electrical life	8.000 hours
Neon tube light intensity	Lumen 200 (8W) - Lumen 420 (13W)
Neon tube type and colour temperature	T5 - 6400K
Rated insulation voltage	Ui 300V - Uimp 2.5KV
On-Off switch	Built-in
Light up possibility	Through door limit switch - 050F02S
Accessory	050S019 Magnetic mounting plate
Spare parts	Neon tube 050TNE8(8W),050TNE13(13W),050TNE21(21W)

Lamp wiring	Included. 4m of orange cable 2x1.5 + 1x1.5mm ²
Sockets	type CEE 7/3 - 250V-10A max
Warranty period	18 months

Disegni tecnici

