

## Datablad

### 050PPE8

Fluorescerende lineaire plafondlamp met VDE stopcontacten, 8W, 240V, 50/60HZ, 200 lm, L 450 mm



## Kenmerken

<b>Bereik</b>	Plafondlampen met VDE connectors
<b>Component</b>	Fluorescerende plafondlamp, VDE stopcontact.,8W,240V,50/60HZ
<b>Rubriek</b>	050PPE8
<b>Omschrijving</b>	Fluorescerende lineaire plafondlamp met VDE stopcontacten, 8W, 240V, 50/60HZ, 200 lm, L 450 mm
<b>Kleur</b>	Grigio RAL7035
<b>Gewicht</b>	990,0
<b>Douanetarief</b>	85393980
<b>GTIN</b>	8052878049423

## Technische gegevens

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN60598-1,IEC-EN60598-2-1
<b>Compliance with standards</b>	IEC-EN62471
<b>Compliance to EMC standards</b>	EN55015, EN61000-3-2, EN61000-3-3, EN61547
<b>Compliance to directives</b>	2014/35/EU, 2014/30/EU, RoHS 2011/65/EU
<b>Operating temperatures</b>	-10° ÷ +50°C
<b>Protection degree</b>	IP20 (IEC-EN60529)
<b>Protection against impact</b>	IK03 (IEC-EN62262)
<b>Housing material</b>	Metal: Aluminum / Thermoplastic: PP Polypropylene
<b>Protection against electric shock</b>	Class I (IEC-EN61140)
<b>Operating voltage tolerance</b>	-20% / +10%
<b>Neon tube electrical life</b>	8.000 hours
<b>Neon tube light intensity</b>	Lumen 200 (8W) - Lumen 420 (13W)
<b>Neon tube type and colour temperature</b>	T5 - 6400K
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV
<b>On-Off switch</b>	Built-in
<b>Light up possibility</b>	Through door limit switch - 050F02S
<b>Accessory</b>	050S019 Magnetic mounting plate
<b>Spare parts</b>	Neon tube 050TNE8(8W),050TNE13(13W),050TNE21(21W)

---

<b>Lamp wiring</b>	Included. 4m of orange cable 2x1.5 + 1x1.5mm <sup>2</sup>
<b>Sockets</b>	type CEE 7/3 - 250V-10A max
<b>Warranty period</b>	18 months

---

## Technische tekeningen

