

## Datasheet

050TLBA

Connection module for signal tower



## Features

<b>Range</b>	Modular signal towers
<b>components</b>	Connection module
<b>Code</b>	050TLBA
<b>Description</b>	Connection module for signal tower
<b>Colour</b>	Grigio RAL7016
<b>Weight - gr</b>	165.0
<b>Customs Tariff</b>	85365080
<b>GTIN</b>	8052878065775

## Datasheet

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP44 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Housing material</b>	PA Polyamide
<b>Terminal screw</b>	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
<b>Terminal screw head shape</b>	Combined:cross Phillips2 or slotted flat D.5mm max
<b>Terminal screw material</b>	Zinc plated steel
<b>Rated insulation voltage</b>	Ui 690V - Uimp 4KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Signalling type</b>	Steady - Up to 5 modules 050TMLx max.
<b>Assembly style</b>	050TLBA + 050TMLx + 050TPxxGR
<b>Warranty period</b>	18 months

# Technical drawings

