

## Datablad

050TMLA24

Module met oranje vast licht , 24V AC/DC



## Kenmerken

<b>Bereik</b>	Modulaire lichtkolommen
<b>Component</b>	Modules met vast licht, 24V
<b>Rubriek</b>	050TMLA24
<b>Omschrijving</b>	Module met oranje vast licht , 24V AC/DC
<b>Kleur</b>	Arancio
<b>Gewicht</b>	154,0
<b>Douanetarief</b>	85365080
<b>GTIN</b>	8052878071356

## Technische gegevens

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Compliance with standards</b>	IEC-EN62471
<b>Compliance to EMC standards</b>	EN55015, EN61000-3-2, EN61000-3-3, EN61547
<b>Operating temperatures</b>	-25° ÷ +65°C
<b>Protection degree</b>	IP44 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Housing material</b>	PC Polycarbonate
<b>Combustion behaviour</b>	V2 (UL94)
<b>Rated insulation voltage</b>	Ui 690V - Uimp 4KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Signalling type</b>	Steady - Up to 5 modules 050TMLx max.
<b>Assembly style</b>	050TLBA + 050TMLx + 050TPxxxGR
<b>Lighting type</b>	LED bulb
<b>Bulb base</b>	Ba15d bayonet (IEC-EN60061-1)
<b>Available models</b>	AC/DC 24V-62.5mA-1.5W, AC/DC 230V-13mA-3W
<b>Operating voltage tolerance</b>	Vn +10% / -20%
<b>Electrical life</b>	30.000h
<b>Luminous flux</b>	200 lm +/-15%
<b>Warranty period</b>	18 months

## Technische tekeningen

