


Hoja de datos

050TMLBL240

Módulo con luz fija azul , 240V AC



Características

| | |
|------------------|------------------------------------|
| Rango | Columnas luminosas desmontables |
| Componente | Módulos con luz fija, 240V |
| Código | 050TMLBL240 |
| Descripción | Módulo con luz fija azul , 240V AC |
| Color | Blu |
| Peso | 154,0 |
| Arancel aduanero | 85365080 |
| GTIN | 8052878071387 |

Datos técnicos

| | |
|-----------------------------------|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards | IEC-EN62471 |
| Compliance to EMC standards | EN55015, EN61000-3-2, EN61000-3-3, EN61547 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP44 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Housing material | PC Polycarbonate |
| Combustion behaviour | V2 (UL94) |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Signalling type | Steady - Up to 5 modules 050TMLx max. |
| Assembly style | 050TLBA + 050TMLx + 050TPxxxGR |
| Lighting type | LED bulb |
| Bulb base | Ba15d bayonet (IEC-EN60061-1) |
| Available models | AC/DC 24V-62.5mA-1.5W, AC/DC 230V-13mA-3W |
| Operating voltage tolerance | Vn -20% / +10% |
| Electrical life | 30.000h |
| Luminous flux | 200 lm +/-15% |
| Warranty period | 18 months |

Dibujos técnicos

