
# Datasheet

050TMLBL24
Blue steady light module, 24V AC/DC





## Features

| | |
|---|---|
| **Range** | Modular signal towers |
| **components** | Steady light modules, 24V |
| **Code** | 050TMLBL24 |
| **Description** | Blue steady light module, 24V AC/DC |
| **Colour** | Blu |
| **Weight - gr** | 154.0 |
| **Customs Tariff** | 85365080 |
| **GTIN** | 8052878071394 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-ENC60947-1, IEC-EN60947-5-1 |
| **Compliance with standards** | IEC-EN62471 |
| **Compliance to EMC standards** | EN55015, EN61000-3-2, EN61000-3-3, EN61547 |
| **Operating temperatures** | -25° ÷ +65°C |
| **Protection degree** | IP44 (IEC-EN60529) |
| **Protection against impact** | IK07 (IEC-EN62262) |
| **Housing material** | PC Polycarbonate |
| **Rated insulation voltage** | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Combustion behaviour** | V2 (UL94) |
| **Signalling type** | Steady - Up to 5 modules 050TMLx max. |
| **Assembly style** | 050TLBA + 050TMLx + 050TPxxxGR |
| **Lighting type** | LED bulb |
| **Bulb base** | Ba15d bayonet (IEC-EN60061-1) |
| **Available models** | AC/DC 24V-62.5mA-1.5W, AC/DC 230V-13mA-3W |
| **Operating voltage tolerance** | Vn -20% / +10% |
| **Electrical life** | 30.000h |
| **Luminous flux** | 200 lm +/-15% |
| **Warranty period** | 18 months |

## Technical drawings

