

Datenblatt

050TMLI24

Dauerlichtmodul farblos , 24V AC/DC



Merkmale

Baureihe	Zusammenstellbare Meldeleuchtensäulen
Komponenten	Dauerlichtmodul, 24V
Artikel-Nr.	050TMLI24
Beschreibung	Dauerlichtmodul farblos , 24V AC/DC
Farbe	Incolore
Gewicht - gr	154,0
Zolltarifnummer	85365080
GTIN	8052878071370

Technische Daten

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62471
Compliance to EMC standards	EN55015, EN61000-3-2, EN61000-3-3, EN61547
Operating temperatures	-25° ÷ +65°C
Protection degree	IP44 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Housing material	PC Polycarbonate
Combustion behaviour	V2 (UL94)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Signalling type	Steady - Up to 5 modules 050TMLx max.
Assembly style	050TLBA + 050TMLx + 050TPxxxGR
Lighting type	LED bulb
Bulb base	Ba15d bayonet (IEC-EN60061-1)
Available models	AC/DC 24V-62.5mA-1.5W, AC/DC 230V-13mA-3W
Operating voltage tolerance	Vn -20% / +10%
Electrical life	30.000h
Luminous flux	200 lm +/-15%
Warranty period	18 months

Technische Zeichnungen

