


## Datasheet

050TMLV240

Green steady light module, 240V AC



## Features

|                       |                                    |
|-----------------------|------------------------------------|
| <b>Range</b>          | Modular signal towers              |
| <b>components</b>     | Steady light modules, 240V         |
| <b>Code</b>           | 050TMLV240                         |
| <b>Description</b>    | Green steady light module, 240V AC |
| <b>Colour</b>         | Verde                              |
| <b>Weight - gr</b>    | 154.0                              |
| <b>Customs Tariff</b> | 85365080                           |
| <b>GTIN</b>           | 8052878071448                      |

## Datasheet

|  |  |
|--|--|
| <b>Approvals</b>                         | CE   |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1            |
| <b>Compliance with standards</b>         | IEC-EN62471                                |
| <b>Compliance to EMC standards</b>       | EN55015, EN61000-3-2, EN61000-3-3, EN61547 |
| <b>Operating temperatures</b>            | -25° ÷ +65°C                               |
| <b>Protection degree</b>                 | IP44 (IEC-EN60529)                         |
| <b>Protection against impact</b>         | IK07 (IEC-EN62262)                         |
| <b>Housing material</b>                  | PC Polycarbonate                           |
| <b>Combustion behaviour</b>              | V2 (UL94)                                  |
| <b>Rated insulation voltage</b>          | Ui 690V - Uimp 4KV (IEC-EN60947-1)         |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                     |
| <b>Signalling type</b>                   | Steady - Up to 5 modules 050TMLx max.      |
| <b>Assembly style</b>                    | 050TLBA + 050TMLx + 050TPxxxGR             |
| <b>Lighting type</b>                     | LED bulb                                   |
| <b>Bulb base</b>                         | Ba15d bayonet (IEC-EN60061-1)              |
| <b>Available models</b>                  | AC/DC 24V-62.5mA-1.5W, AC/DC 230V-13mA-3W  |
| <b>Operating voltage tolerance</b>       | Vn -20% / +10%                             |
| <b>Electrical life</b>                   | 30.000h                                    |
| <b>Luminous flux</b>                     | 200 lm +/-15%                              |
| <b>Warranty period</b>                   | 18 months                                  |

## Technical drawings

