


## Datenblatt

### 050ULSQ9

Beleuchtete Sicherheitseinheit, Direktversorgung, 400V AC/DC 2W, BA9S LED-Lampe nicht im Lieferumfang enthalten



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Einzelkomponenten   |
| <b>Komponenten</b>     | Beleuchtete Sicherheitseinheit  |
| <b>Artikel-Nr.</b>     | 050ULSQ9  |
| <b>Beschreibung</b>    | Beleuchtete Sicherheitseinheit, Direktversorgung, 400V AC/DC 2W, BA9S LED-Lampe nicht im Lieferumfang enthalten |
| <b>Farbe</b>           | Rosso   |
| <b>Gewicht - gr</b>    | 38,0  |
| <b>Zolltarifnummer</b> | 85365080  |
| <b>GTIN</b>            | 8052878068691   |

## Technische Daten

|                                   |   |
|-----------------------------------|---|
| <b>Approvals</b>                  | CE  |
| <b>Compliance with standards</b>  | IEC-ENC60947-1, IEC-EN60947-5-1                                     |
| <b>Operating temperatures</b>     | -25° ÷ +65°C  |
| <b>Protection against impact</b>  | IK03 (IEC-EN62262)  |
| <b>Protection degree</b>          | IP65 front light / IP20 terminals (IEC-EN60529)                     |
| <b>Shock resistance</b>           | 30g duration=18ms (EN-IEC 60068-2-27)                               |
| <b>Shock resistance</b>           | 50g duration=11ms (EN-IEC 60068-2-27)                               |
| <b>Vibration resistance</b>       | 5g f= 2...500Hz (EN-IEC 60068-2-6)                                  |
| <b>Housing material</b>           | PA Polyamide  |
| <b>Lens material</b>              | PC Polycarbonate  |
| <b>Locking ring material</b>      | Zamak zinc alloy  |
| <b>Fixing diameter</b>            | 22.5mm - Thickness 1÷6mm  |
| <b>Terminal screw</b>             | Tightening torque 0.8÷1 Nm (IEC-EN60947-1)                          |
| <b>Terminal screw head shape</b>  | Combined:cross Phillips2 or slotted flat D.5mm max                  |
| <b>Terminal screw material</b>    | Zinc plated steel   |
| <b>Terminal screw connections</b> | min 1x0.5mm <sup>2</sup> (20AWG) - max 2x2.5mm <sup>2</sup> (14AWG) |
| <b>Cable lugs</b>                 | Fork type "spring spade" for screw M3.5 / W=6.4mm                   |
| <b>Bulb type</b>                  | Ba9S 400V - 2W max (not included)                                   |
| <b>Rated insulation voltage</b>   | Ui 690V - Uimp 4KV (IEC-EN60947-1)                                  |

---

**Protection against electric shock**

Class II (IEC-EN61140)

---

**Warranty period**

18 months

---

## Technische Zeichnungen

