


Scheda Dati

050ULSQ9

Valaistu turvayksikkö, suorasyöttö, 400V AC/DC 2W BA9S LED-lamppu ei sisälly toimitukseen



Caratteristiche

| | |
|------------------|---|
| Range | Yksittäiset komponentit |
| Componente | Valaistu turvayksikkö |
| Code | 050ULSQ9 |
| Kuvaus | Valaistu turvayksikkö, suorasyöttö, 400V AC/DC 2W BA9S LED-lamppu ei sisälly toimitukseen |
| Väriä | Rosso |
| Peso | 38,0 |
| Tariffa doganale | 85365080 |
| GT | 8052878068691 |

Dati tecnici

| | |
|----------------------------|---|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -25° ÷ +65°C |
| Protection against impact | IK03 (IEC-EN62262) |
| Protection degree | IP65 front light / IP20 terminals (IEC-EN60529) |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Housing material | PA Polyamide |
| Lens material | PC Polycarbonate |
| Locking ring material | Zamak zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Terminal screw | Tightening torque 0.8÷1 Nm (IEC-EN60947-1) |
| Terminal screw head shape | Combined:cross Phillips2 or slotted flat D.5mm max |
| Terminal screw material | Zinc plated steel |
| Terminal screw connections | min 1x0.5mm ² (20AWG) - max 2x2.5mm ² (14AWG) |
| Cable lugs | Fork type "spring spade" for screw M3.5 / W=6.4mm |
| Bulb type | Ba9S 400V - 2W max (not included) |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |

Protection against electric shock

Class II (IEC-EN61140)

Warranty period

18 months

Disegni tecnici

