


Scheda Dati

050ULSQ9

Unidade de segurança iluminada, alimentação direta, 400V AC/DC 2W, lâmpada LED BA9S não incluída



Caratteristiche

Gama	Componentes únicos
Componente	Unidade luminosa de segurança
Código	050ULSQ9
Descrição	Unidade de segurança iluminada, alimentação direta, 400V AC/DC 2W, lâmpada LED BA9S não incluída
Cor	Rosso
Peso	38,0
Tariffa doganale	85365080
GTIN	8052878068691

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection against impact	IK03 (IEC-EN62262)
Protection degree	IP65 front light / IP20 terminals (IEC-EN60529)
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Housing material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	Zamak zinc alloy
Fixing diameter	22.5mm - Thickness 1÷6mm
Terminal screw	Tightening torque 0.8÷1 Nm (IEC-EN60947-1)
Terminal screw head shape	Combined:cross Phillips2 or slotted flat D.5mm max
Terminal screw material	Zinc plated steel
Terminal screw connections	min 1x0.5mm ² (20AWG) - max 2x2.5mm ² (14AWG)
Cable lugs	Fork type "spring spade" for screw M3.5 / W=6.4mm
Bulb type	Ba9S 400V - 2W max (not included)
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)

Protection against electric shock

Class II (IEC-EN61140)

Warranty period

18 months

Disegni tecnici

