

## Scheda Dati

### 060APTLRC

Pulsante di emergenza a palmo, luminoso, momentaneo tasto bombato rosso, con custodia



## Caratteristiche

|                         |                                                     |
|-------------------------|-----------------------------------------------------|
| <b>Gamma</b>            | Pulsanti di emergenza a palmo luminosi              |
| <b>Componente</b>       | Pulsanti a palmo con tasto bombato con custodia     |
| <b>Codice</b>           | 060APTLRC                                           |
| <b>Descrizione</b>      | Pulsante di emergenza a palmo, luminoso, momentaneo |
| <b>Colore</b>           | Rosso                                               |
| <b>Peso</b>             | 373,0                                               |
| <b>Tariffa doganale</b> | 85365080                                            |
| <b>GTIN</b>             | 8052878050573                                       |

## Dati tecnici

|                                                    |                                                                     |
|----------------------------------------------------|---------------------------------------------------------------------|
| <b>Approvals</b>                                   | CE, UL, CSA                                                         |
| <b>Compliance with standards</b>                   | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5                 |
| <b>Compliance with standards</b>                   | IEC-ENC60947-1, IEC-EN60947-5-1                                     |
| <b>Compliance with standards</b>                   | UNI CEI EN 45545-2                                                  |
| <b>Operating temperatures</b>                      | -30° ÷ +120°C                                                       |
| <b>Environmental operating values</b>              | +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)                        |
| <b>Protection degree</b>                           | IP66 - IP69 (IEC-EN60529)                                           |
| <b>Protection against impact</b>                   | IK08 (IEC-EN62262)                                                  |
| <b>Mechanical durability</b>                       | 3.000.000 Operations                                                |
| <b>Button/mushroom material (illuminated type)</b> | PC Polycarbonate                                                    |
| <b>Housing material</b>                            | PA Polyamide V0 (UL94)                                              |
| <b>Gasket material</b>                             | Cork rubber                                                         |
| <b>Screw material</b>                              | Stainless steel AISI 304                                            |
| <b>Cover screws tightening torque</b>              | 1 ÷ 2.5Nm (8.8÷22.1 Lb-in)                                          |
| <b>Terminal screw</b>                              | Tightening torque 0.8÷1 Nm (IEC-EN60947-1)                          |
| <b>Terminal screw head shape</b>                   | Combined: cross Phillips2 or slotted flat D.5mm max                 |
| <b>Terminal screw material</b>                     | Zinc plated steel                                                   |
| <b>Terminal screw connections</b>                  | min 1x0.5mm <sup>2</sup> (20AWG) - max 2x2.5mm <sup>2</sup> (14AWG) |
| <b>Actuation possibilities</b>                     | By hand, elbow or foot                                              |
| <b>For illuminated version</b>                     | LED circuit 24V AC-DC 25mA                                          |

|                                                |                                                                   |
|------------------------------------------------|-------------------------------------------------------------------|
| <b>LED connections for illuminated version</b> | min 1x0.25mm <sup>2</sup> (22AWG)- max 1x1mm <sup>2</sup> (17AWG) |
| <b>Contact material</b>                        | Ag 1000/1000                                                      |
| <b>Contact movement</b>                        | Slow action contact                                               |
| <b>Contacts</b>                                | Self cleaning by pads creeping                                    |
| <b>NC contacts (all versions)</b>              | Positive opening function (IEC-EN60947-5-1 ann.K)                 |
| <b>Rated insulation voltage</b>                | Ui 690V - Uimp 4KV (IEC-EN60947-1)                                |
| <b>Rated thermal current</b>                   | Ith 10A (IEC-EN60947-1)                                           |
| <b>Electrical ratings</b>                      | AC15-DC13 (IEC-EN60947-5-1) - A600-P300 (UL 508)                  |
| <b>AC Performances</b>                         | AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A                           |
| <b>DC Performances</b>                         | DC 24V-5A, 120V-1.1A, 240V-0.55A                                  |
| <b>Contact block</b>                           | 1NO+1NC Included                                                  |
| <b>Halogen-free</b>                            | yes                                                               |
| <b>Warranty period</b>                         | 18 months                                                         |

## Disegni tecnici

