

Fiche technique

060C2MA

Poste de commande bimanuelle, gris, aluminium



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | Dispositifs de commande à deux mains |
| Composant | Console de commande bimanuelle en aluminium |
| Code | 060C2MA |
| Désignation des marchandises | Poste de commande bimanuelle, gris, aluminium |
| Couleur | Grigio RAL7016 |
| Poids | 2050,0 |
| Tarif douanier | 85371098 |
| GTIN | 8052878050825 |

Données techniques

| | |
|--|---|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards | IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851 |
| Operating temperatures | -40° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Manufacturing process | Diecasting |
| Material | Aluminum Al Si 12 |
| Screw material | Stainless steel AISI 304 |
| Painting | Polyester powder coating |
| Operators plate material | Anodized aluminum - thickness 2mm |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Pushbutton characteristics | See the single items 020PTFAR-020PTFFGR-020GE11 |
| Safety accessory | 060MCP2M - 2 hand simultaneous action controller |
| Floor-mount stand / support | Articles 060SCO or 060SCDO |
| Warranty period | 18 months |

Dessins techniques

