

Scheda Dati

060C2MAA

Twee hand bedieningsconsole, oranje, aluminium



Caratteristiche

Bereik	Tweehandenbediening
Componente	Twee hand bedieningsconsole in aluminium
Rubriek	060C2MAA
Omschrijving	Twee hand bedieningsconsole, oranje, aluminium
Kleur	Arancio
Peso	2050,0
Tariffa doganale	85371098
GTIN	8052878068578

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	Stainless steel AISI 304
Painting	Polyester powder coating
Operators plate material	Anodized aluminum - thickness 2mm
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Floor-mount stand / support	Articles 060SCO or 060SCDO
Warranty period	18 months

Disegni tecnici

