

Fiche technique

060C2MGRP

Poste de commande bimanuelle avec boutons-poussoirs, gris, aluminium



Caractéristiques

Portée	Dispositifs de commande à deux mains
Composant	Console de commande bimanuelle en aluminium, avec BP
Code	060C2MGRP
Désignation des marchandises	Poste de commande bimanuelle avec boutons-poussoirs, gris, aluminium
Couleur	Grigio RAL7016
Poids	2040,0
Tarif douanier	85371098
GTIN	8052878067397

Données techniques

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	Stainless steel AISI 304
Painting	Polyester powder coating
Operators plate material	Anodized aluminum - thickness 2mm
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Floor-mount stand / support	Articles 060SCO or 060SCDO
Warranty period	18 months

Dessins techniques

