# Datasheet

060CL2MA
Sloped two-hand control panel, grey, aluminium



## Features

| | |
|---|---|
| **Range** | Two-hand control devices |
| **components** | Aluminium sloped two-hand control panel |
| **Code** | 060CL2MA |
| **Description** | Sloped two-hand control panel, grey, aluminium |
| **Colour** | Grigio RAL7016 |
| **Weight - gr** | 1461.0 |
| **Customs Tariff** | 85371098 |
| **GTIN** | 8052878050887 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-ENC60947-1, IEC-EN60947-5-1 |
| **Compliance with standards** | IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851 |
| **Operating temperatures** | -40° ÷ +70°C |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Manufacturing process** | Diecasting |
| **Material** | Aluminum Al Si 12 |
| **Screw material** | Zamak zinc alloy |
| **Screw type** | M10 - slotted head type 6mm flat blade |
| **Painting** | Polyester powder coating |
| **Rated insulation voltage** | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| **Protection against electric shock** | Class I (IEC-EN61140) |
| **Pushbutton characteristics** | See the single items 020PTFAR-020PTFFGR-020GE11 |
| **Safety accessory** | 060MCP2M - 2 hand simultaneous action controller |
| **Floor-mount stand / support** | Articles 060SCO+060PAP or 060SCDO+060PAP |
| **Warranty period** | 18 months |

## Technical drawings




