

Hoja de datos

060CL2MA

Estación de mando bimanual, inclinada, gris, aluminio



Características

| | |
|------------------|---|
| Rango | Dispositivos de mando con dos manos |
| Componente | Estación de mando bimanual inclinada de aluminio |
| Código | 060CL2MA |
| Descripción | Estación de mando bimanual, inclinada, gris, aluminio |
| Color | Grigio RAL7016 |
| Peso | 1461,0 |
| Arancel aduanero | 85371098 |
| GTIN | 8052878050887 |

Datos técnicos

| | |
|-----------------------------------|---|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards | IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851 |
| Operating temperatures | -40° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Manufacturing process | Diecasting |
| Material | Aluminum Al Si 12 |
| Screw material | Zamak zinc alloy |
| Screw type | M10 - slotted head type 6mm flat blade |
| Painting | Polyester powder coating |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Pushbutton characteristics | See the single items 020PTFAR-020PTFFGR-020GE11 |
| Safety accessory | 060MCP2M - 2 hand simultaneous action controller |
| Floor-mount stand / support | Articles 060SCO+060PAP or 060SCDO+060PAP |
| Warranty period | 18 months |

Dibujos técnicos

