

Scheda Dati

060CL2MA
Kallistettu harmaa kahden käden hallintalaite, alumiini



Caratteristiche

Range	Kaksikäätiset ohjauslaitteet
Componente	Alumiininen kallistettu kahden käden hallintalaite
Code	060CL2MA
Kuvaus	Kallistettu harmaa kahden käden hallintalaite, alumiini
Väriä	Grigio RAL7016
Peso	1461,0
Tariffa doganale	85371098
GT	8052878050887

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	Zamak zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Painting	Polyester powder coating
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Floor-mount stand / support	Articles 060SCO+060PAP or 060SCDO+060PAP
Warranty period	18 months

Disegni tecnici

