

Fiche technique

060CL2MA

Pupitre de commande bimanuelle incliné, gris, aluminium



Caractéristiques

Portée	Dispositifs de commande à deux mains
Composant	Pupitre de commande bimanuelle incliné en aluminium
Code	060CL2MA
Désignation des marchandises	Pupitre de commande bimanuelle incliné, gris, aluminium
Couleur	Grigio RAL7016
Poids	1461,0
Tarif douanier	85371098
GTIN	8052878050887

Données techniques

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	Zamak zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Painting	Polyester powder coating
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Floor-mount stand / support	Articles 060SCO+060PAP or 060SCDO+060PAP
Warranty period	18 months

Dessins techniques

