Scheda Dati

060CL2MA
Pulsantiera a due mani inclinata, grigia, alluminio



Caratteristiche

Gamma	Dispositivi di comando a due mani
Componente	Pulsantiera a due mani inclinata in alluminio
Codice	060CL2MA
Descrizione	Pulsantiera a due mani inclinata, grigia, alluminio
Colore	Grigio RAL7016
Peso	1461,0
Tariffa doganale	85371098
GTIN	8052878050887

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	Zamak zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Painting	Polyester powder coating
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Floor-mount stand / support	Articles 060SCO+060PAP or 060SCDO+060PAP
Warranty period	18 months

Disegni tecnici



