

Scheda Dati

060CL2MAA

Estação de comando bimanual, inclinada, alaranjado, alumínio



Caratteristiche

Gama	Dispositivos de comando a duas mãos
Componente	Estação de comando bimanual inclinada em alumínio
Código	060CL2MAA
Descrição	Estação de comando bimanual, inclinada, alaranjado, alumínio
Cor	Arancio
Peso	1461,0
Tariffa doganale	85371098
GTIN	8052878068561

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	Zamak zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Painting	Polyester powder coating
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Floor-mount stand / support	Articles 060SCO+060PAP or 060SCDO+060PAP
Warranty period	18 months

Disegni tecnici

