


Datasheet

060CT2MAGR

Two-hand control station Techno 70, grey, thermoplastic



Features

Range	Two-hand control devices
components	Two-hand control station in thermoplastic
Code	060CT2MAGR
Description	Two-hand control station Techno 70, grey, thermoplastic
Colour	Grigio RAL7016
Weight - gr	550.0
Customs Tariff	85371098
GTIN	8052878078515

Datasheet

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK09 (IEC-EN62262)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technical drawings

