


## Hoja de datos

060CT2MAGR

Pulsador bimanual Techno 70, gris, termoplástico



## Características

<b>Rango</b>	Dispositivos de mando con dos manos
<b>Componente</b>	Pulsador bimanual en termoplástico
<b>Código</b>	060CT2MAGR
<b>Descripción</b>	Pulsador bimanual Techno 70, gris, termoplástico
<b>Color</b>	Grigio RAL7016
<b>Peso</b>	550,0
<b>Arancel aduanero</b>	85371098
<b>GTIN</b>	8052878078515

## Datos técnicos

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Compliance with standards</b>	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items from family 020 / CMD&SIGN; SM2 Ø22
<b>Warranty period</b>	18 months

# Dibujos técnicos

