


## Hoja de datos

060CT2MAGR

Pulsador bimanual Techno 70, gris, termoplástico



## Características

Rango	Dispositivos de mando con dos manos
Componente	Pulsador bimanual en termoplástico
Código	060CT2MAGR
Descripción	Pulsador bimanual Techno 70, gris, termoplástico
Color	Grigio RAL7016
Peso	550,0
Arancel aduanero	85371098
GTIN	8052878078515

## Datos técnicos

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK09 (IEC-EN62262)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

# Dibujos técnicos

