# Fiche technique

060MLP2GR
Modules simple pour commande bimanuelle, inclinés, gris, aluminium



## Caractéristiques

| | |
|---|---|
| **Portée** | Dispositifs de commande à deux mains |
| **Composant** | Modules individuels inclinés, commande bimanuelle, aluminium |
| **Code** | 060MLP2GR |
| **Désignation des marchandises** | Modules simple pour commande bimanuelle, inclinés, gris, aluminium |
| **Couleur** | Grigio RAL7016 |
| **Poids** | 1300,0 |
| **Tarif douanier** | 85371098 |
| **GTIN** | 8052878067489 |

## Données techniques

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-ENC60947-1, IEC-EN60947-5-1 |
| **Compliance with standards** | IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851 |
| **Operating temperatures** | -40° ÷ +70°C |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Manufacturing process** | Diecasting |
| **Enclosure material** | Aluminum Al Si11 Cu2 (EN AC46100) |
| **Gasket material** | Nitrile rubber |
| **Screw material** | Zamak zinc alloy |
| **Screw type** | M10 - slotted head type 6mm flat blade |
| **Tightening torque** | 2,5Nm (22.1 Lb-in) |
| **Painting** | Polyester powder coating |
| **Rated insulation voltage** | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| **Protection against electric shock** | Class I (IEC-EN61140) |
| **Safety accessory** | 060MCP2M - 2 hand simultaneous action controller |
| **Pushbutton characteristics** | See the single items 020PTFFGR and 020GE11 |
| **Packaging** | 2 modules (left - right unit) |
| **Warranty period** | 18 months |

## Dessins techniques




