

Scheda Dati

060P2MAA

Pupitre de commande bimanuelle, protégé, orange, aluminium



Caratteristiche

| | |
|-------------------------------------|--|
| Portée | Dispositifs de commande à deux mains |
| Componente | Pupitre de commande bimanuelle protégé en aluminium |
| Code | 060P2MAA |
| Désignation des marchandises | Pupitre de commande bimanuelle, protégé, orange, aluminium |
| Couleur | Arancio |
| Peso | 4650,0 |
| Tariffa doganale | 85371098 |
| GTIN | 8052878067380 |

Dati tecnici

| | |
|--|---|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards | IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851 |
| Operating temperatures | -40° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK10 (IEC-EN62262) |
| Manufacturing process | Shell gravity diecasting |
| Enclosure material | Aluminum Al Si11 Cu2 (EN AC46100) |
| Screw material | Stainless steel AISI 304 |
| Wrist support material | Stainless steel AISI 304 |
| Black base material | Steel |
| Operators plate material | Painted steel - thickness 1.5mm |
| Painting | Polyester powder coating |
| Rated insulation voltage | Ui 690V - Uimp 4KV (IEC-EN60947-1) |
| Protection against electric shock | Class I (IEC-EN61140) |
| Pushbutton characteristics | See the single items 020PTAASRK-020PTF9MGR-020GE11 |
| Safety accessory | 060MCP2M - 2 hand simultaneous action controller |
| Accessories | Sealing screws 060VCE |
| Floor-mount telescopic stand | Articles 060STP2M OR 060STP2MA |
| Warranty period | 18 months |

Disegni tecnici

