

## Fiche technique

060P2MEAGR

Boîtier de commande bi-manuel, ergonomique, gris, en aluminium



## Caractéristiques

<b>Portée</b>	Dispositifs de commande à deux mains
<b>Composant</b>	Boîtier de commande bi-manuel, protégé, ergonomique
<b>Code</b>	060P2MEAGR
<b>Désignation des marchandises</b>	Boîtier de commande bi-manuel, ergonomique, gris, en aluminium
<b>Couleur</b>	Grigio RAL7016
<b>Poids</b>	2980,0
<b>Tarif douanier</b>	85371098
<b>GTIN</b>	8052878074555

## Données techniques

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Compliance with standards</b>	IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851
<b>Operating temperatures</b>	-40° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK10 (IEC-EN62262)
<b>Manufacturing process</b>	Shell gravity diecasting
<b>Enclosure material</b>	Aluminum Al Si11 Cu2 (EN AC46100)
<b>Screw material</b>	Stainless steel AISI 304
<b>Wrist support material</b>	Stainless steel AISI 304
<b>Black base material</b>	Steel
<b>Operators plate material</b>	Painted steel - thickness 1.5mm
<b>Painting</b>	Polyester powder coating
<b>Rated insulation voltage</b>	Ui 690V - Uimp 4KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class I (IEC-EN61140)
<b>Pushbutton characteristics</b>	See the single items 020PTAASRK-020PTF9MGR-020GE11
<b>Safety accessory</b>	060MCP2M - 2 hand simultaneous action controller
<b>Accessories</b>	Sealing screws 060VCE
<b>Floor-mount telescopic stand</b>	Articles 060STP2M OR 060STP2MA
<b>Warranty period</b>	18 months

# Dessins techniques

